




BIDWELL WALNUT




OIL FINISH


STANDARD FINISHES



POLY FINISH



OIL FINISH



NORDIC
WALNUT



CUSTOM
FINISHES
ALSO AVAILABLE

DESCRIPTION

The rich color & deep grain of walnut is unmistakable and has been highly prized throughout history. It is the only tree we know of named for a Greek god (Jupiter). With the addition of our ThinClad collection of products, we offer this wood for flooring as well, making it an all-around choice for stunning interior applications.

SPECIES

Juglans regia and Juglans nigra

MILLWORK

Surfaced 4 sides with tongue and groove profile. Flooring products are back-relieved & end matched. ThinClad planks have a micro-bevel T&G.

FLOORING + CLADDING DIMENSIONS

SOLID: 3/4" thick x 3, 4 & 5" mixed widths x 1'-6' solid random lengths (or longer, if available)

ENGINEERED: 5/8" thick x (specified width) x 1'-6' random lengths. Wear layer 5/32" (4mm) thick over a 1/2" (12mm) thick plywood substrate

THINCLAD CLADDING DIMENSIONS

3/8" thick x 3, 4 & 5" mixed widths x 1'-6' solid random lengths (or longer, if available)

SOURCE


Recovered and upcycled byproduct from walnut orchards in the western US

SUSTAINABILITY

LEED V4
Building Product Disclosure & Optimization
Regional Priority
Low-Emitting Materials
Material Ingredients

DECLARE LABEL: Red List Approved for oil, poly & unfinished

GREENGUARD GOLD: Standard Oil & Poly Finishes are Greenguard Gold Certified



HARDNESS

Black Walnut Janka rating 1010, English Walnut 1200. Suitable for high-traffic indoor environments

GRADE

Insect holes, tight knots, split knots, occasional staining/discoloration & unlimited color & grain variation including sapwood & infrequent spalted wood

FLAME SPREAD

Class C. Class A flame retardant coatings are available

APPLICATION

Flooring, Interior Cladding, Stair Treads, Tables, Benches and Custom Applications

MINIMUM ORDER


250 sq.ft. or 500 sq.ft. for engineered

LEAD TIME

2-6 Weeks (or less)

Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	OTHER WIDTH(S)	THICKNESS	FINISH	GRADE	PROFILE
Flooring + Interior Cladding	3, 4 & 5" Mixed	3-8"	3/4" Thick	Unfinished, Oil or Poly	Character	T+G
ThinClad Interior Cladding	3, 4 & 5" Mixed	3-8"	3/8" Thick	Unfinished, Oil or Poly	Character	T+G Micro-Bevel
Engineered Flooring	3, 4 & 5" Mixed	3-8"	5/8" Thick	Unfinished, Oil or Poly	Character	T+G Micro-Bevel
Custom widths & profiles are available. Custom factory stains and finishes available on all products.					Inquire to create your custom specification	



TONGUE + GROOVE

Standard profile (other profiles available)




T+G: MICRO BEVEL

Standard on most engineered products, recommended for most pre-finished items & wall cladding



T+G: THINCLAD MICRO-BEVEL

Recommended for interior wall cladding



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor



FINISHES

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

CUSTOMIZATION

We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look. Please inquire.

PATTERNS

We can manufacture engineered products in a variety of patterns, including chevron and herringbone patterns.



LIVING FUTURE
CORPORATE MEMBER



ANTHOLOGY WOODS



1.800.293.8178
www.anthologywoods.com
info@anthologywoods.com