




OXLEY OAK



STANDARD FINISH:



DESCRIPTION

Oxley Oak combines the sophistication of a modern finish with the distinctive character of reclaimed oak. An homage to the timeless look of aged European fumed oak, you'll see unique color, grain and depth from the lightly textured surface. Pre-finished with a specialty natural oil finish, it makes any floor or cladding installation a breeze and lends a pedigree of effortless elegance. Wire brushed texture, pronounced grain.

MILLWORK

Surfaced 4 sides with profile as per specification. Flooring products are back-relieved and end-matched. Custom millwork and dimensions are available.

FLOORING + CLADDING DIMENSIONS

SOLID: 3/4" thick x (specified width) x 1'-10' solid random lengths (or longer, if available)

ENGINEERED: 5/8" thick x (specified width) x 1'-10' random lengths. Wear layer 5/32" (4mm) thick over a 1/2" (12mm) thick plywood substrate

THINCLAD CLADDING DIMENSIONS

3/8" thick x 5" face width x 1'-10' solid random lengths (or longer, if available)

SOURCE

Various sources depending on wood substrate. FSC® reclaimed, salvaged and FSC new wood options are available.

SUSTAINABILITY

FSC® CERTIFIED:

Recycled or Mixed available upon request

LEED V4

Building Product Disclosure & Optimization

Regional Priority

Building Life-Cycle Impact Reduction

Low-Emitting Materials

Material Ingredients

HARDNESS

White Oak Janka rating: 1360

GRADE

Depends on wood substrate. Select & Character grade available. Call for options.

FLAME SPREAD

White Oak: 100 (Class C). Class A flame retardant coatings are available.

APPLICATION

Interior Wall & Ceiling Cladding, Flooring & Custom Applications

MINIMUM ORDER

250 sq.ft. or 500 sq.ft. for engineered.


LEAD TIME

2-6 weeks (or less)



Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	OTHER WIDTH(S)	THICKNESS	GRADE	PROFILE
Solid Flooring + Cladding	5" Fixed	3-10"	3/4" Thick	Select or Character	T+G
ThinClad Interior Cladding	5" Fixed	3, 4, 5" Mixed	3/8" Thick	Select or Character	T+G
Engineered Flooring + Cladding	5" Fixed	3-10"	5/8" Thick	Select or Character	T+G Micro-Bevel
A variety of fixed and mixed widths are available up to 10" wide. Please inquire for more information.				Inquire to create your custom specification	




TONGUE + GROOVE

Standard profile (other profiles available)



T+G: MICRO BEVEL

Standard on most engineered products, recommended for most pre-finished items & wall cladding



T+G: THINCLAD MICRO-BEVEL

Recommended for interior wall cladding



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor



FINISHES

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

CUSTOMIZATION



We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look. Please inquire.

PATTERNS

We can manufacture the engineered product in a variety of patterns, including chevron and herringbone patterns.



LIVING FUTURE
CORPORATE MEMBER



ANTHOLOGY WOODS

1.800.293.8178
www.anthologywoods.com
info@anthologywoods.com