




PACIFIC GOLDEN OAK




CARMEL FINISH

STANDARD FINISHES



POLY FINISH



CARMEL FINISH



CUSTOM FINISHES
ALSO AVAILABLE

DESCRIPTION

This rugged beauty is an Oregon native and available in wonderfully wide widths. As a "rescued" product from conifer harvest in the Pacific Northwest, Pacific Golden Oak is rich in color and character. For flooring, it is considerably harder than common White Oak from the eastern United States. You'll see a variety of grain patterns, knots and checks, and colors ranging from luminous soft wheat, strawberry blonde & red ochre.

SPECIES

Notholithocarpus densiflorus

MILLWORK

Surfaced 4 sides, tongue & groove. Flooring products are back-relieved & end matched. ThinClad planks have a micro-bevel T&G.

FLOORING + CLADDING DIMENSIONS

SOLID: 3/4" thick x (specified width) x 1'-10' solid random lengths (or longer, if available)

ENGINEERED: 5/8" thick x (specified width) x 1'-10' random lengths (or longer, if available). Wear layer 5/32" (4mm) thick over a 1/2" (12mm) thick plywood substrate

THINCLAD DIMENSIONS

3/8" thick x 5" face width x 1'-10' solid random lengths (or longer, if available)

SOURCE

Recovered and upcycled byproduct from contemporary harvest of conifer trees in Pacific Northwest

SUSTAINABILITY

LEED V4

Building Product Disclosure & Optimization
Regional Priority

Low-Emitting Materials

Material Ingredients

DECLARE LABEL: Red List Approved for Unfinished, Oil & Poly Finish

GREENGUARD GOLD: Standard Oil & Poly Finishes are Greenguard Gold Certified

HARDNESS

Janka rating 1420. Suitable for high-traffic indoor environments.

GRADE

Natural color & grain variation, bright sapwood & a variety of fillable defects including surface checks, sound knots & open character

FLAME SPREAD

Not tested. Class A flame retardant coatings are available

APPLICATION


Flooring, Interior Cladding, Stair Treads & Custom Applications

MINIMUM ORDER

250 sq.ft. or 500 sq.ft. minimum for engineered

LEAD TIME

2-6 weeks (or less)




Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	OTHER WIDTH(S)	THICKNESS	FINISH	PROFILE
Flooring + Interior Cladding	5" Fixed	3-8"	3/4" Thick	Unfinished, Oil, Poly or Carmel Finish	T+G
ThinClad Interior Cladding	5" Fixed	3, 4, & 5" Mixed	3/8" Thick	Unfinished, Oil, Poly or Carmel Finish	T+G Micro-Bevel
Engineered Flooring	5" Fixed	3-8"	5/8" Thick	Unfinished, Oil, Poly or Carmel Finish	T+G Micro-Bevel

Fixed and mixed widths are available from 3" to 8" wide (and wider in limited availability). Custom profiles are available. Product may be engineered in quantities of 800 sq. ft. or greater. Please inquire for more information.

Inquire to create your custom specification



TONGUE + GROOVE

Standard profile (other profiles available)




T+G: MICRO BEVEL

Standard on most engineered products, recommended for most pre-finished items & wall cladding



T+G: THINCLAD MICRO-BEVEL

Recommended for interior wall cladding



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor



FINISHES

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

CUSTOMIZATION

We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look. Please inquire.

PATTERNS

We can manufacture engineered products in a variety of patterns, including chevron and herringbone patterns.



LIVING FUTURE
CORPORATE MEMBER



ANTHOLOGY WOODS

1.800.293.8178
www.anthologywoods.com
info@anthologywoods.com