





PELA TEAK



STANDARD FINISHES



UNFINISHED



OIL FINISH



CUSTOM
FINISHES
ALSO AVAILABLE

DESCRIPTION

This beautiful reclaimed teak from Southeast Asia is already filled with the wisdom of the ages and is best installed completely bare. It will continue to patina and age over time, sharing its unassuming, elegant character with the next generation to come. The brushed smooth surface retains an aged & naturally distressed texture for a wall or floor filled with history.

SPECIES

Tectona grandis

MILLWORK

Surfaced 3 sides, tongue & groove with micro-bevel, end-matched. Custom millwork available.

FLOORING + CLADDING DIMENSIONS

5/8" thick x 3, 4 & 5" face width x 1'- 10' solid random lengths (or longer, if available). Wear layer 4mm thick over a 10mm thick plywood substrate.

LEAD TIME

2-6 weeks (or less) if in stock, 3-4 months (or less) if not in stock

SOURCE

Post-consumer reclaimed from sources including pole-houses, warehouses and industrial buildings in Asia

SUSTAINABILITY

FSC® CERTIFIED: Recycled

LEED V4

Building Product Disclosure & Optimization

Building Life-Cycle Impact Reduction

Low-Emitting Materials

Material Ingredients



HARDNESS

Teak Janka rating 1075. Heavy traffic is likely to impact the flooring surface and contribute to the beauty, patina and character over time.

GRADE

Infrequent to frequent filled small fastener holes, insect holes, tight knots or filled split knots. Occasional staining or discolorations & other signs of previous use. Surface has natural patina & variation in color & texture as expected with an S3S product.

FLAME SPREAD

USDA FSI Teak: 76 (Class C). Class A flame retardant coatings are available.

APPLICATION

Flooring, Interior Cladding, Stair Treads, & Custom Applications. Inquire for details.

MINIMUM ORDER

250 sq.ft.

Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	THICKNESS	FINISH	PROFILE
Engineered Cladding	3, 4 & 5" Mixed	5/8" Thick	Unfinished, Oil or Poly Finish	T+G: Micro Bevel

This product is showcased for installation without finish. It will continue to naturally patina and build added character and beauty over time. PLEASE NOTE: finish will darken wood. Custom finish options are available. Custom profiles and widths are available for quantities exceeding 5000 square feet.

Inquire to create your custom specification



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor or for wall paneling



FINISHES

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

CUSTOMIZATION

We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look. Please inquire.

PATTERNS

We can manufacture the engineered product in a variety of patterns, including chevron and herringbone patterns.



LIVING FUTURE
CORPORATE MEMBER

Declare.



ANTHOLOGY WOODS



1.800.293.8178
www.anthologywoods.com
info@anthologywoods.com