## SPECIFIER'S GUIDE + TECHNICAL DATA

# **SAKHAY TEAK**



#### STANDARD FINISHES









#### **DESCRIPTION**

Sakhay Teak is synonymous with premium. For centuries, teak has been prized for its beauty, strength and durability. Today you can recapture the simple elegance of old-growth FSC® Certified reclaimed teak. Rich honey, tan, carmel and espresso brown accent the warm color tones in a lively mixed grain. A smooth surface with the supple texture distinctive to teak and its natural oil content.

#### **SPECIES**

Tectona grandis

#### **MILLWORK**

Surfaced 4 sides with tongue & groove profile. Flooring products are back-relieved & end-matched. ThinClad planks have a micro-bevel T&G.

#### FLOORING + CLADDING DIMENSIONS

SOLID: 3/4" thick x 4-1/4" face width x 1'-10' solid and random lengths (or longer, if available)

ENGINEERED: 5/8" thick x 4-1/4" face width x 1'-10' solid random lengths (or longer, if available). Wear layer 4mm thick over a 10mm thick plywood substrate.

#### THINCLAD DIMENSIONS

3/8" thick x 4-1/2" face width x 1'-10' solid and random lengths (or longer, if available)

#### **LEAD TIME**

2-6 weeks (or less) if in stock, 3-4 months (or less) if not in stock.

#### SOURCE

Post-consumer reclaimed from sources including pole-houses, warehouses & industrial buildings in Asia

#### **SUSTAINABILITY**

FSC® CERTIFIED: Recycled

#### LEED V4

Building Product Disclosure & Optimization Building Life-Cycle Impact Reduction Low-Emitting Materials Material Ingredients

**DECLARE LABEL:** Red List Approved for Unfinished, Poly Finish & Oil Finish

GREENGUARD GOLD: Standard Oil & Poly Finishes are Greenguard Gold Certified







#### **HARDNESS**

Teak Janka rating 1075. Heavy traffic is likely to impact the flooring surface and contribute to the beauty, patina & character over time.

#### **GRADE**

Infrequent to frequent filled small fastener holes, insect holes, tight knots, or filled split knots. Occasional staining or discoloration & other signs of previous use. Holes & voids are pre-filled with teak and/or teak sanding dust mixed with glue.

#### **FLAME SPREAD**

USDA FSI Teak: 76 (Class C). Class A flame retardant coatings are available.

#### **APPLICATION**


Flooring, Interior Cladding, Stair Treads, Tables, Benches, Siding, Decking & Custom Applications. Inquire for details.

#### **MINIMUM ORDER**


250 sq.ft. for solid. 500 sq.ft. for engineered.

Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	THICKNESS	FINISH	PROFILE
Flooring + Interior Cladding	4-1/4" Face Width	3/4" Thick	Unfinished, Oil or Poly	T+G
Engineered Flooring	4-1/4" Face Width	5/8" Thick	Unfinished, Oil or Poly	T+G Micro-Bevel
ThinClad Paneling	4-1/2" Face Width	3/8" Thick	Unfinished, Oil or Poly	T+G Micro-Bevel
Widths up to 7" wide and custom profiles are available (2,000 square feet minimum order). Custom factory stains and finishes available on all products. Oil finish in place recomended for best results with solid flooring. Please inquire.			Inquire to create your custom specification	




TONGUE + GROOVE
Standard profile (other profiles available)




T+G: MICRO BEVEL

Standard on most engineered products, recommended for most pre-finished items & wall cladding



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor



T+G: THINCLAD MICRO-BEVEL Recommended for interior wall cladding



#### **FINISHES**

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

#### **CUSTOMIZATION**

We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look.

Please inquire.

#### **PATTERNS**

We can manufacture the engineered product in a variety of patterns, including chevron and herringbone patterns.









### **ANTHOLOGY WOODS**

















1.800.293.8178 www. anthologywoods.com info@anthologywoods.com