




SAWMILL OAK




POLY FINISH


STANDARD FINISHES



UNFINISHED



POLY FINISH



OIL FINISH



DESCRIPTION

Sawmill Oak embraces the rich patina inherent to reclaimed wood. Sourced from barns, out-buildings, warehouses, factories and other sources, it retains the natural and man-made characteristics that embody a true reclaimed spirit. Deep grooves, checks, saw-trace marks and frequent oxide stains evoke the American Pioneer Spirit.

SPECIES

Quercus alba and Quercus rubra

MILLWORK

S3S with partial saw-traced patina surface. Level of patina may be customized. Profile as per specification. Flooring products are back-relieved & end-matched. Custom millwork & dimensions are available.

FLOORING + CLADDING DIMENSIONS

SOLID: 5/8" thick x (specified width) x 1'-10' solid random lengths (or longer, if available)

ENGINEERED: 5/8" thick x (specified width) x 1'-10' solid random lengths (or longer, if available). Wear layer 5/32"(4mm) thick over 1/2" (12mm) thick plywood substrate.

THINCLAD CLADDING DIMENSIONS

3/8" thick x 3, 4 & 5" mixed widths x 1'-10' solid random lengths (or longer, if available)

SOURCE

Post-consumer FSC Certified Recycled from sources including barns, out-buildings, warehouses & factories.

SUSTAINABILITY

FSC® CERTIFIED: Recycled

LEED V4

Building Product Disclosure & Optimization
Regional Priority

Building Life-Cycle Impact Reduction

Low-Emitting Materials

Material Ingredients

DECLARE LABEL: Red List Approved for Unfinished, Oil & Poly Finish

GREENGUARD GOLD: Standard Oil & Poly Finishes are Greenguard Gold Certified

HARDNESS

White Oak Janka rating 1360, Red Oak Janka rating 1290. Suitable for high-traffic indoor environments.

GRADE

Infrequent to frequent fastener holes, insect holes, surface texture, tight knots or filled split knots, occasional staining or discoloration & other signs of previous use.

FLAME SPREAD

USDA FSI Red Oak: 100; White Oak: 100 (class C). Class A flame retardant coatings are available.

APPLICATION


Flooring, Interior Cladding, Stair Treads, Tables, Benches & Custom Applications.

MINIMUM ORDER

250 sq.ft. or 500 sq.ft. for engineered.


LEAD TIME

2-6 Weeks (or less)



Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	OTHER WIDTH(S)	THICKNESS	FINISH	PROFILE
Flooring + Interior Cladding	5" Fixed	3-8"	5/8" Thick	Unfinished, Oil or Poly	T+G
ThinClad Interior Cladding	3, 4, 5" Mixed	5" Fixed	3/8" Thick	Unfinished, Oil or Poly	T+G
Engineered Flooring	5" Fixed	3-8"	5/8" Thick	Unfinished, Oil or Poly	T+G Micro-Bevel
A variety of fixed and mixed widths are available up to 10" wide. Custom factory stains and finishes available on all products. Oil finish in place recommended for best results with solid flooring. Please inquire for more information.				Inquire to create your custom specification	



TONGUE + GROOVE

Standard profile (other profiles available)



T+G: MICRO BEVEL

Standard on most engineered products, recommended for most pre-finished items & wall cladding



T+G: THINCLAD MICRO-BEVEL

Recommended for interior wall cladding



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor



FINISHES

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

CUSTOMIZATION


We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look. Please inquire.

PATTERNS

We can manufacture the engineered product in a variety of patterns, including chevron and herringbone patterns.



LIVING FUTURE
CORPORATE MEMBER



ANTHOLOGY WOODS

1.800.293.8178
www.anthologywoods.com
info@anthologywoods.com